



- Socket device IP65 or rubber capped IP54 for increased protection
- Easy installation with mountable socket device
- Thread adapters for special threads

hex 27 accessories

	 Rubber protective cap with two cable feeds for 1.7 to 2.3 mm diameter cable When rubber cap attached IP54 Suitable for voltages up to 42 V	 Socket device Threaded connection Pg9 (Tightening range 6 - 9 mm) When attached to socket device IP65 Suitable for voltages up to 250 V	 Socket device with indicator light According to DIN EN 175301- 803-A (DIN 43650) Threaded connection Pg9 (Tightening range 6 - 9 mm) When attached to socket device IP65 Suitable for 24 V or 250 V	 Thread adapter for special threads from G1/4-DIN3852-E to R1/4 acc. to DIN 2999 including FKM seals
0170 / 0171	■	■		■
0180 / 0181	■ (Up to max 42 V)	■		■
0183	■ (Up to max 42 V)	■		
0184 / 0185			■ 24 V or 250 V (upon request) see also page 33	■
0190 / 0191	■	■		■
0194 / 0195			■ (24 V on request) also see page 35	■
0186 / 0187	■ (Up to max 42 V)	■		■
0196 / 0197	■	■		■
Order number:	1-1-70-621-007	1-1-80-652-002	24 VDC: 1-1-84-652-011	1-1-00-420-009

250 VAC: 1-1-84-652-010